HAR44EL

FALL ARRESTER HARNESS WITH BELT - 4 ANCHORAGE POINTS - DIELECTRIC

Ref. HAR44EL_

Product specifications

Dielectric harness with positioning belt. 2 fall arrester anchorage points (back - front). 4 adjustable buckles. Positioning belt with thermoformed back closed with wide Velcro for more comfort. 180° rotation. 2 lateral anchorage points for work positioning. Sponge back lining. Buckles with plastic coating. Material insulates to 20kV.

Straps: Polyester.
Buckles: 100% plastic coating.

COLOUR
Black-Grey

SIZE
S/M/L, XL/XXL

Product Use - Risks

Fall

Construction / Civil engineering Heavy industry Services / Logistics

Oil / Gas Wind energy

Vertical movement on a permanent structure Long vertical movement or movement on inclined surface Short vertical movement or movement on inclined surface (less than 3 m) Vertical movement, confined space Long movement with multi connection /disconnection Work positioning Movement on lifeline Restraint Long horizontal movement on horizontal surface Long horizontal movement on vertical structure Short horizontal movement (less than 3 m)

Product's highlights & user's benefits

	DIELECTRIC
	2 accessory attachment holders incorporated into the belt
	Rotation 180°

Certifications and Standards

CE

PPE DIRECTIVE EC 89/686

EN363 : 2008 Personal fall protection equipment - Personal fall protection systems

EN364 : 1992 Personal fall protection equipment : Test method

EN365 : 2004 General requirements for the instructions for use and the marking

EN361 : 2002 Personal protection equipment against falls from a height - Full body harnesses

EN358 : 1999 Personal fall protection equipment for work positioning and prevention of falls from a hight - Belts for work positioning and restraint and work positioning lanyards.

References

References	Bar code	COLOUR	SIZE		
HAR44ELGT	3295249203504	Black-Grey	S/M/L	5	-
HAR44ELXX	3295249204723	Black-Grey	XL/XXL	5	-